

PREFIXCMD (PREFIXFIL) : Exclude Commands (Files) from Prefetch/Multifetch Processing

Parameter	Specify . . .	Possible Values	Default
<u>PREFIXCMD</u>	the commands to exclude from prefetch processing.	L1-L9	none
<u>PREFIXFIL</u>	the files to exclude from prefetch processing.	1-5000	none

Together, PREFIXFIL and PREFIXCMD specify one or more files to be excluded from prefetch/multifetch processing. PREFIXFIL specifies one or more files by file number; PREFIXCMD specifies a command for each file number.

You can either "include" list of files using PREFIFIL/PREFICMD) or "exclude" lists of files using the parameters PREFIXFIL/PREFIXCMD, depending on which list is shorter. You cannot both include and exclude files at the same time.

If prefetching/multifetching has been specified and

- files/commands have been neither included nor excluded, the prefetching/multifetching applies to all files by default.
- files/commands have been excluded using PREFIXFIL/PREFIXCMD, the prefetching/ multifetching applies only to the files on the "exclusion" list.
- both PREFIFIL/PREFICMD and PREFIXFIL/PREFIXCMD are specified, Adabas recognizes the exclusion parameters PREFIXFIL/PREFIXCMD and ignores the inclusion parameters PREFIFIL/PREFICMD.

Example:

Exclude the L3 command for file 8 from prefetch processing.

```
ADARUN PREFIXFIL=8 , PREFIXCMD=L3
```

Multiple Exclusions

Specify multiple file numbers in multiple PREFIXFIL statements or in a list, separated by commas. Specify multiple commands in multiple PREFIXCMD statements or in a list, separated by slashes (/). The maximum number of entries for each is 50.

If you use lists, they must have the same number of entries. There is a one-to-one correspondence, by position, between a file number in the PREFIXFIL list and a command in the PREFIXCMD list.

Example:

Exclude the L3 command for file 8 and the L3 and L9 commands for file 12 from prefetch/multifetch processing.

```
ADARUN PREFIXFIL=8,12,12,PREFIXCMD=L3/L3/L9
```

or

```
ADARUN PREFIXFIL=8,PREFIXCMD=L3
  ADARUN PREFIXFIL=12,PREFIXCMD=L3
  ADARUN PREFIXFIL=12,PREFIXCMD=L9
```

As the preceding example shows, you can specify the same file number several times, with a different command each time. Likewise, you can specify the same command code several times, with a different file number each time.

Eligible Commands and Command Pairs

The following commands can be excluded from prefetch/multifetch processing for a file:

- L1/L4
- L2/L5
- L3/L6
- L9

If either command in one of the pairs above is specified in a PREFIXCMD statement, *both* commands are excluded. For example, if PREFIXCMD=L1 is specified, both L1 and L4 are excluded.

Example:

Execute a user program with multifetch and allocate 20,000 bytes for the total prefetch buffer area. Exclude the L3 and L6 commands for files 8 and 12 from multifetch processing. Exclude *all* commands for file 7.

```
ADARUN PROG=USER,PREFETCH=YES,PREFTB=20000
  ADARUN PREFIXFIL=8,12,PREFIXCMD=L3/L3
  ADARUN PREFIXFIL=7,7,7,7,PREFIXCMD=L1/L2/L3/L9
```

No PREFSBL value is specified, so the buffer length for a single prefetch sequence defaults to 3,000 bytes; up to 6 prefetch sequences can be handled.